

ELC12-28 (12V 28Ah)

Specifications

Nominal Voltage	12V		
Nominal Capacity(20 Hr)	28Ah		
Dimension	Length	166±1mm(6.54 inches)	
	Width	175±1mm(6.89 inches)	
	Containeriner Height	126±1mm(4.96 inches)	
	Total Height	126±1mm(4.96 inches)	
Approx Weight	Approx8.3kgs(18.30 lbs)		
Design life	10 years		
Terminal	M6		
Container Material	ABS		
Rated Capacity	28.00Ah/1.40A	(20hr, 1.80V/Cell, 25 °C/77°F)	
	26.18Ah/2.62A	(10hr, 1.80V/Cell, 25 °C/77°F)	
	23.00Ah/4.60A	(5hr, 1.75V/Cell, 25 °C/77°F)	
	16.60Ah/16.60A	(1hr, 1.60V/Cell, 25 °C/77°F)	
Max. Discharge Current	280A(5s)		
Internal Resistance	Appro≤12.5mΩ		
Operating Temp. Range	Discharge: -20 °C~50 °C		
	Charge: -20 °C~50 °C		
	Storage: -20 °C~50 °C		
Nominal Operating Temp. Range	25±3 °C(77±5°F)		
Cycle Use	Initial Charging Current Less than 6.5A. Voltage		
	14.4V-15.0V at 25 °C(77°F) Temp. Coefficient-		
Standby Use	No limit on Intital Charging Current Voltage 13.5V-		
	13.8V at 25 °C(77°F) Temp. Coefficient-20mV/C		
Capacity affected by Temperature	40 °C(104°F)	103%	
	25 °C(77°F)	100%	
	0 °C(32°F)	86%	
Self Discharge	ELC series batteries may be stored for up to 6 months at25 °C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.		



Application

- ♦ All purpose
- ♦ Uninterruptable Power Supply(UPS)
- ♦ Electric Power System(EPS)
- ♦ Emergency backup power supply
- ♦ Emergency light
- ♦ Railway signal
- ♦ Aircraft signal
- ♦ Alarm and securitysystem
- ♦ Electronic apparatus & equipment
- ♦ Communication power supply
- ♦ DC power supply
- ♦ Auto controlsystem

Constant Current Discharge (Amperes) at 25 °C (77°F)



F.V/Time	15min	30min	45min	1h	2h	3h	5h	6h	8h	10h	20h
1.60V	46.9	27.6	20.9	16.6	9.8	7.2	4.8	4.2	3.3	2.7	1.44
1.67V	44.3	26.2	20.1	16.1	9.4	6.9	4.8	4.1	3.3	2.7	1.43
1.70V	41.6	25.4	19.4	15.5	9.2	6.8	4.7	4.1	3.2	2.7	1.41
1.75V	39.0	24.3	18.5	14.8	8.9	6.6	4.6	4.0	3.2	2.6	1.39
1.80V	36.6	23.4	17.9	14.3	8.6	6.4	4.5	3.9	3.1	2.6	1.38

Constant Power Discharge (Watts) at 25 °C (77°F)


F.V/Time	15min	30min	45min	1h	2h	3h	5h	6h	8h	10h	20h
1.60V	89.7	54.9	39.8	31.8	18.5	13.7	9.3	8.1	6.4	5.3	2.8
1.67V	85.9	51.5	38.4	31.0	18.0	13.3	9.2	8.0	6.4	5.3	2.8
1.70V	80.0	50.3	37.2	29.9	17.6	13.0	9.0	7.9	6.3	5.2	2.8
1.75V	75.1	47.9	35.7	28.8	17.2	12.8	8.9	7.8	6.2	5.2	2.8
1.80V	70.5	46.0	34.5	27.9	16.6	12.4	8.7	7.6	6.2	5.1	2.7

ELC12-28 (12V 28Ah)


Dimensions




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle life in Relation to Depth of Discharge



Self-discharge Characteristics



Specifications subject to change without prior notice.