

ELC12-5 (12V 5Ah)

Specification

Nominal Voltage	12V	
Nominal Capacity(20 Hr)	5.0Ah	
Dimension	Length	90±1mm(3.54 inches)
	Width	70±1mm(2.76 inches)
	Containeriner Height	101±1mm(3.98 inches)
	Total Height (With terminal)	107±1mm(4.21 inches)
	Approx Weight	Approx 1.58 kgs(3.48 lbs)
Design life	5 years	
Terminal	F1	
Container Material	ABS	
Rated Capacity	5.0Ah/0.25A	(20hr, 1.75V/Cell, 25 °C/77°F)
	4.7Ah/0.47A	(10hr, 1.80V/Cell, 25 °C/77°F)
	4.45Ah/0.89A	(5hr, 1.75V/Cell, 25 °C/77°F)
	3.26Ah/3.26A	(1hr, 1.60V/Cell, 25 °C/77°F)
Max. Discharge Current	75.0A(5s)	
Internal Resistance	Appro≤25.0mΩ	
Operating Temp. Range	Discharge: -20 °C~50 °C	
	Charge: -20 °C~50 °C	
	Storage: -20 °C~50 °C	
Nominal Operating Temp. Range	25±3 °C(77±5°F)	
Cycle Use	Initial Charging Current Less than 1.50A. Voltage 14.4V-14.9V at 25 °C(77°F) Temp. Coefficient-20mV/C	
	No limit on Intital Charging Current Voltage 13.6V-13.8V at 25 °C(77°F) Temp. Coefficient-20mV/C	
Standby Use	40 °C(104°F)	103%
Capacity affected by Temperature	25 °C(77°F)	100%
	0 °C(32°F)	86%
	ELC series batteries may be stored for up to 6 months at25 °C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Application

- ◆ All purpose
- ◆ Uninterruptable Power Supply(UPS)
- ◆ Electric Power System(EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and securitysystem
- ◆ Electronic apparatus & equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto controlsystem

Constant Current Discharge (Amperes) at 25 °C (77F)



F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	19.96	13.09	9.61	5.70	4.16	3.26	2.06	1.41	0.94	0.63	0.50	0.264
1.67V	19.01	12.54	9.40	5.61	4.09	3.16	2.03	1.39	0.93	0.62	0.49	0.259
1.70V	18.21	11.86	9.27	5.53	4.04	3.06	1.99	1.36	0.91	0.61	0.49	0.255
1.75V	17.36	11.31	8.78	5.35	3.93	2.96	1.95	1.34	0.89	0.60	0.48	0.250
1.80V	16.03	10.53	8.19	5.14	3.80	2.88	1.88	1.29	0.86	0.59	0.47	0.247

Constant Power Discharge (Watts) at 25 °C (77F)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	37.16	25.11	18.57	11.09	8.11	6.42	4.05	2.79	1.87	1.26	1.00	0.527
1.67V	35.61	24.10	18.21	10.94	8.01	6.20	3.98	2.74	1.83	1.25	0.99	0.519
1.70V	34.15	22.79	18.01	10.81	7.93	5.98	3.91	2.69	1.80	1.23	0.99	0.513
1.75V	32.71	21.76	17.09	10.49	7.74	5.76	3.83	2.64	1.77	1.22	0.97	0.502
1.80V	30.50	20.35	15.97	10.10	7.50	5.54	3.68	2.53	1.70	1.18	0.96	0.500



ELC12-5 (12V 5Ah)

Dimensions





Discharge Characteristics

Float Charging Characteristics





Temperature Effects in Relation to Battery Capacity

Effect of Temperature on Long Term Float Life



Cycle life in Relation to Depth of Discharge

Self-discharge Characteristics



- A** No supplementary charge required.
(Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
3. Charged for 8-10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.